



Microbarometer digital MB3d	per 1	12,865
Weight and Dimensions: H 25 cm / Diam. 11 cm / Weight 3.4 Kg	per 2	12,750
Transducer block + Digital hood	per 3	12,620
	per 4	12,500
	from 5 to 9	12,350
	from 10 to 19	11,835



Microbarometer analog MB3a	per 1	9,260
Weight and Dimensions H 13.6 cm / Diam. 11 cm / Weight 3.0 Kg	per 2	9,160
Transducer block + Analog hood	per 3	9,060
	per 4	8,950
	from 5 to 9	8,850
	from 10 to 19	8,230

PACK-TUB-FOAM	ScrewPack with foam	Plastic tube packaging	130
PELI1430_1S	PELICASE 1430 1 sensor	PELICASE 1430 + adapted foam / Dim. int : 344 x 146 x 297 mm / Dim. ext : 430 x 244 x 341 mm	650
TMG-DET-3-73	PELICASE 1650 6 sensors	PELICASE 1650 + adapted foam / Int Dim : L725 x W445 x D270 mm / Ext Dim : L802 x W520 x D316 mm	1,250



MB3a

from **€6990** EX-VAT EX-WORKS
for 30 units

ORDER NOW

Tel. : +33 (0)2 96 46 16 11
marketing@seismowave.com

SEISMOWAVE.COM

SERVICES

**AFTER SALES ASSISTANCE
HOTLINE WARRANTY**

**METROLOGY
(using IS calibrator®)**

MAINTENANCE

ask for a quotation

- Seismometers: for 30 years
- Microbarometers: for 20 years

SOFTWARE

DIONISOS-MU-001	Dionisos Software V1.03	It enables monitoring, parameter set-up, data transfer, real-time acquisition and signal processing	695
-----------------	-------------------------	---	-----

MANUAL

TUG	Technical User Guide	Paper Book edition	60
UMD	Dionisos User Manual	Paper Book edition	70

CABLES



PR000187-CBL_3	12 V Power cable	RSN801 - 3 pin connector to fast on 3 m long	232
PR000183-CBL_5	GPS cable 5 m	RSN279 - Coaxial TNC to TNC 5 m long	150
PR000183-CBL_10	GPS cable 10m	RSN279 - Coaxial TNC to TNC 10 m long	170
PR000188-CBL_1,5	PC/USB cable 1,5 m	RSN819 - 18 pin to USB 1.5 m long	245
PR000187-CBL_3	PC/USB cable 3 m	RSN819 - 18 pin to USB 3 m long	260
PR000161-CBL_3	Sensor to digitizer cable	RSN804 - 18 pin to not wired 3 m long	260

TOOLS



PR0000826-CBL	Magnet Adjustment Cable	18 pin connector to banana plugs. To connect between the analog module and a multimeter in order to adjust the magnet position.	150
MU000384	Magnet Wrench	Wrench designed to adjust the position of the magnet	55

ACCESSORIES



ANT_PROC_2000B	GPS ANTENNA PRO-COM 2000B TNC	Built-in high gain, low noise amplifier / Right-hand circular polarization (RHCP) / 3 V / TNC / EMC tested	110
PE9560	Right Angle Adapter	Right angle adaptor for GPS antenna TNC Male to TNC Male	90
BAT_YUASA 12V12AH	BATTERY NP12-12 YUASA	12Ah / 12V / Lead Acid / 97.5 X 98 X 151mm / 4kg / Max: 3A	110

DIGITAL STARTER KIT

- **MB3d**
- **12V power cable 3m**
- **Signal cable 1.5m**
- **GPS antenna with right angle adapter**
- **12V battery**
- **Magnet wrench**
- **Dionisos software**
- **User guide**
- **Transport case**



~~€15,050~~

€ **14,200** EX-VAT EX-WORKS

ORDER NOW

Tel. : +33 (0)2 96 46 16 11
marketing@seismowave.com